



# Silver Hawk Type II Sprinter 2500



## CHASSIS

- Dodge Sprinter 2500, 144" WB, 8,550 GVWR
- Front Axle- 3970 GAWR, Rear Axle- 5360 GAWR
- Mercedes Benz 3.0L CRD V-6 Diesel engine
- Automatic 5-Speed transmission
- Rear Axle- 3.91:1 gear ratio
- Alternator- Bosch 220 amp
- 25-gallon fuel capacity
- 225/75R16.0 black sidewall tires
- Spare tire- matching
- OEM High Roof
- Sliding curbside door- 51.75"W x 77.5"H opening
- Power door locks- Power windows
- Power operated side mirrors w/convex, turn signals
- Tilt/Telescoping steering wheel
- AM/FM/CD radio with 4-speakers
- Dual Captain's chairs with tilt back
- Gray rubber formed floor mats
- Auxiliary A/C compressor
- Back-Up Alarm- 97 decibel

## CHASSIS EXTERIOR

- MEDIX painted rear bumper w/flip-up center step
- OEM fixed front and rear mud flaps

## ENVIRONMENTAL SYSTEMS

- Combination 43.6K BTU heat, 32K BTU A/C updraft system ducted down through upper cabinetry
- 580 CFM multi-speed fan
- External auxiliary condenser mounted under body
- Exhaust fan- 2-speed, 520 CFM

## POWER DISTRIBUTION & CONTROL

- OEM dual battery system
- Digital volt/amp meter
- Basic, easy maintenance relay/circuit breaker system
- Color-coded, stamped label wiring

- Front Console, floor-mounted aluminum body
- Rear control panel mounted in Action Area
- Shoreline- 125V-20 amp covered receptacle
- Battery charger- prewire
- Inverter- prewire w/universal mounting bracket
- 125V outlets- (2)
- 12VDC outlets- (2)
- Radio Power/Ground- (2) with antenna coax

## EMERGENCY LIGHTING & SIREN

- Light Bar, front- Code 3 FM 9000 LED (4) red, (1) clear
- Exterior Body- 9x7 Red LEDs on corners each side, 9x7 Red LEDs each corner rear, 9x7 Amber LEDs (2) rear,
- Grille/Intersection- (2) 7x3 LEDs, (2) 5x2 LEDs in corner housing on bumper, (2) 7x3 LEDs on fenders.
- Interior, Rear Doors- When doors are open, 5x2 Red LEDs (2), (1) 5x2 Amber LED, (2) 26-degree load lights
- Scene Lights- (4) 7x3 LEDs
- Hand-held Spotlight- 400K candle power, in cab
- Siren- 200 watt w/NC microphone in front console
- Siren Speakers- (2) 100 watt in front bumper skirt

## PATIENT COMPARTMENT INTERIOR

- Formed fiberglass ceiling panel
- Formed fiberglass curbside wall panel
- Laminated wood cabinetry
- Acrylic sliding doors with full height extruded pull handles
- Patient Compartment- Interior Headroom- 75"
- Cabinet to Squad Bench Aisle- 38"
- Cab to Patient Compartment walk-thru
- Patient Compartment Insulation- 2.5" fiberglass batting
- Sound deadening foam applied to wheel wells

- Squad Bench- (3) belted seating positions, rear access to slide-out Oxygen cylinder bracket.
- QuikNet soft storage above squad bench head pad
- Backboard Storage- 7" vertical slot accessible thru curbside door, holds 16" or 18" boards and scoop stretcher.
- ALS Cabinet- multi-level
- Technician's Seat- rear facing automotive style chair w/integral three-point shoulder harness/lap belt, on steel storage base.
- Interior Lighting- (8) Halogen dome lights recessed in ceiling w/5-minute check-out timer; 12" dual-switch incandescent bar light in Action Area.

## PATIENT CARE SYSTEMS

- Suction Aspirator- disposable container and hose hard plumbed to 12V vacuum pump.
- Oxygen outlets- (2) in Action Area, (1) over Squad Bench
- Oxygen Cylinder Storage- Located under squad bench on slide-out, tilt-down bracket.
- IV Holders- (2) rubber, fold-down recessed in ceiling
- Cot Mount- FW # 175-5, single position, removable

## PAINT, DECAL, LETTERING

- SOL Decals- optional
- Paint Stripe- optional
- Lettering- optional

## WARRANTIES

### CONVERSION:

- Electrical- 72 months/72,000 miles
- Limited- 12 months/12,000 miles
- Paint- if applicable- 48 months